Parkdeck

SYSTEM PLANNING GUIDE

Parking-deck protection with crack-bridging, salt resistance, and defined drive lanes.

Planning guidance only. Not a certified TDS, SDS, purchase specification or mixing recipe. Obtain the selected manufacturer's current documents before application.

01 / SYSTEM AT A GLANCE

System: Parking deck waterproofing / wear system

Use: Car parks, ramps, exposed decks

Indicative thickness: 3 – 8 mm

Substrate: Concrete decks and ramps

Finish: UV-stable wear coat

02 / MATERIALS TO SPECIFY

1. Compatible primer and concrete repairs
2. Specified waterproof / crack-bridging membrane
3. Traffic-bearing resin and graded aggregate
4. UV-resistant finish for exposed areas
5. Drain, joint, kerb and lane-marking materials

03 / CHECK BEFORE ORDERING

Assess exposure, movement, waterproofing, drainage and ramp gradients with the system supplier.

Record floor area, surface condition, moisture testing, repairs, joints, temperature / humidity and site access. Confirm compatibility, consumption per layer, waste allowance, pot life, recoat windows and cure times with the supplier.

Equipment: suitable preparation and dust extraction, approved mixing / application tools and PPE specified by the SDS. Application by trained installers.

floorosmani@gmail.com | +389 70 620 566 | 1205 Vrapciste

Parkdeck / Project form

SYSTEM PLANNING GUIDE

Fill in, save and email this sheet to floorosmani@gmail.com. Leave unknown technical values blank for the site assessment.

Name / company

Email / phone

Project address / area (m²)

Existing surface / moisture / cracks / joints

Traffic / loads / water / chemical exposure

Colour / finish / slip requirement

Access / preferred dates / allowed downtime

Supplier / product codes / quantities for each layer (to confirm)

Questions / site notes / documents required

Attach site photos and request the final TDS, SDS, system build-up and care schedule with your quotation.